

Painting Specification

1) HIGHER SECONDARY SCHOOL BLOCK

Sr. #	Area	Area Sq. Ft.	Painting Process
1	EXTERIOR	34800	STEP-1. WASHING STEP 2. CRACKFILLING STEP-3. PUTTY PATCHUS STEP-4. APPLYING 1 COAT WEATHERCOAT PRIMER STEP 5. APPLYING 2 COATS OF WEATHERSHIELD PROTECT DUST PROOF 6 YEAR
2	INTERIOR	73200	STEP- 1. PAPPERING (REQUIRED AREAS) STEP-2. CRACKFILLING (REQUIRED AREAS) STEP 3. PUTTY PATCHUS (REQUIRED AREAS) STEP-4. APPLYING 1 COAT OFWEATHERCOATPRIMER STEP-5. APPLYING2 COATS OF SUPERCOVER 4 YEARS (WASHABLE)
3	ENAMEL (GLOSS/SATIN)	10200	STEP-1. PAPPERING STEP 2. APPLYING TWO COATS ENAMEL
4	TILE	3000	STEP-1. WASHING STEP-2. APPLYING 2 COATS OF WEATHERSHIELD TILE (SPRY)

2) HIGH SCHOOL BLOCK

Sr. #	Area	Area Sq. Ft.	Painting Process
1	EXTERIOR	32200	STEP-1. WASHING STEP-2. CRACKFILLING STEP-3. PUTTY PATCHUS STEP-4. APPLYING 1 COAT WEATHERCOAT PRIMER STEP-5. APPLYING 2 COATS OF WEATHERSHIELD PROTECT DUST PROOF 6 YEAR
2	INTERIOR	67200	STEP- 1. PAPPERING (REQUIRED AREAS) STEP- 2. CRACKFILLING (REQUIRED AREAS) STEP 3. PUTTY PATCHUS (REQUIRED AREAS) STEP-4. APPLYING 1 COAT OF ALKALI BLOCK PRIMER STEP-5. APPLYING 2 COATS OF SUPERCOVER 4YEAR (WASHABLE)
3	ENAMEL (GLOSS/SATIN)	4950	STEP-1. PAPPERING STEP 2. APPLYING TWO COATS ENAMEL

3) AUDITORIUM

Sr. #	Area	Area Sq. Ft.	Painting Process
1	EXTERIOR	9800	STEP-1. WASHING STEP 2. CRACKFILLING STEP 3. PUTTY PATCHUS STEP 4. APPLYING 1 COAT WEATHERCOAT PRIMER STEP-5. APPLYING 2 COATS OF WEATHERSHIELD PROTECT DUST PROOF 6 YEAR
2	INTERIOR	14400	STEP- 1. PAPPERING (REQUIRED AREAS) STEP- 2. CRACKFILLING (REQUIRED AREAS) STEP 3. PUTTY PATCHUS (REQUIRED AREAS) STEP-4. APPLYING 1 COAT OF ALKALI BLOCK PRIMER STEP 5. APPLYING 2 COATS OF SUPERCOVER 4YEAR (WASHABLE)
3	ENAMEL (GLOSS/SATIN)	1440	STEP-1. PAPPERING STEP 2. APPLYING TWO COATS ENAMEL